

XUUDB MANUAL

UNICORE Team

Document Version:	2.1.1
Component Version:	2.6.2
Date:	15 12 2021

Contents

1	Ove	rview	1
	1.1	The classic mapping	1
	1.2	The dynamic mapping	2
2	Inst	allation	3
	2.1	Installation from Core Server Bundle	3
	2.2	Installation from RPM or DEB packages	3
3	The	XUUDB server	3
	3.1	Security	3
	3.2	Administrative access	4
	3.3	Configuration	4
	3.4	Dynamic mappings configuration	17
	3.5	Starting the XUUDB server	23
	3.6	Stopping the server	23
	3.7	Logging	24
4	The	admin client	26
	4.1	Configuring advanced HTTP client settings	26
	4.2	Commands	30
	4.3	Adding entries using add or adddn	31
	4.4	Checking the content	31
	4.5	Removing entries	31
	4.6	Exporting/importing	32
	17	Undating entries	32

The XUUDB server is an Attribute Source implementation which can be used by UNICORE servers. It is used to map a UNICORE identity (an X500 distinguished name) to authorisation and incarnation attributes. The XUUDB is also capable of performing dynamic mappings of incarnation attributes, using a rule engine.

For more information about UNICORE visit https://www.unicore.eu.

1 Overview

The UNICORE XUUDB is used to map a UNICORE user identity (an X.500 distinguished name (DN)) to a set of attributes. The attributes are typically used to provide local account details (uid, gid(s)) and sometimes also to provide authorization information: user's role.

The UNICORE XUUDB is best suited as a site-service. Theoretically it can be used for multiple sites, however as it offers limited authorization capabilities and doesn't allow for grouping users, it is better to use the more flexible Unity server in such a case. In case of the simple one host-service XUUDB sometimes can be replaced by a simple file storing the mappings. Please refer to the UNICORE/X documentation for more information.

The XUUDB offers two web services, one for querying, and one for administration of the users' database. There are several clients which can use the XUUDB server:

- Admin client (see Section 4) can be used to control the XUUDB database contents.
- UNICORE servers include the XUUDB client code (it is named XUUDB Attribute Information Point) and can consume and process the XUUDB information.

Both admin and client access to the XUUDB can be protected by a client-authenticated SSL.

The XUUDB can map users using two different mechanisms:

- classic or static mechanism, where administrator enters mappings for each DN manually,
- *dynamic* mechanism, where administrator only define rules stating what attributes should be assigned to UNICORE users fulfilling rule's condition.

1.1 The classic mapping

The classic or static mechanism when UNICORE is used as a gateway to HPC site, with a well defined set of users. It is also useful in federated scenarios when a dedicated, external infrastructure is build to maintain a global list of users.

Using it it is possible to set a list of UNIX logins (aka XLogins or uids), a list of UNIX groups (aka projects or gids) and the role attribute used for authorization. The first uid and the first gid is assumed to be the default one but Grid users are allowed to choose any of the available.

In case of the default authorization policy the *user* role is required to get a normal access to the site, the *admin* role grants super-user privileges, and the *banned* role bans the user.

The XUUDB stores and compares only distinguished names (DNs), not full certificates.

Multiple UNICORE sites can share the XUUDB, even if the attributes are different per UNICORE site. Sites are grouped by the so-called GCID (grid component ID).

1.2 The dynamic mapping

The dynamic mechanism is used to map users who were already authorized, therefore it doesn't make sense (and is not possible) to assign the authorization attributes as role. The dynamic mechanism is useful in deployments where a site doesn't know the precise list of its users (which are maintained externally), or simply doesn't want to define local accounts for each UNICORE user. In other words, the site relies on a trusted 3rd party to maintain a list of genuine and authorized users, and automatically assigns a local account to each user.

As it will be shown later on dynamic mappings can be also used in other scenarios, also being complementary to static mappings.

Dynamic mappings configuration is described in the section Section 3.4.

IMPORTANT NOTE ON PATHS

XUUDB is distributed either as an platform independent and portable bundle (as part of the UNICORE quickstart package) or as an installable, platform dependent package such as RPM

Depending on the installation package used paths are different. If installing using distributionspecific package the following path prefixes are used:

```
CONF=/etc/unicore/xuudb
BIN=/usr/sbin
ADMIN=/usr/sbin/unicore-xuudb-admin
LOG=/var/log/unicore/xuudb
```

If installing using portable bundle all XUUDB files are installed under a single directory. Path prefixes used then are as follows, where INST is a directory where the XUUDB was installed:

```
CONF=INST/conf
BIN=INST/bin
ADMIN=BIN/admin.sh
LOG=INST/log
```

The above variables (CONF, BIN, ADMIN and LOG) are used throughout the rest of this manual.

2 Installation

The UNICORE XUUDB is distributed in the following formats:

1. As a part of a platform independent installation bundle called UNICORE core server bundle.

2. As a platform-specific binary package available for RedHat (Centos) and Debian platforms. Those packages are not tested on all possible platforms, but should work without any problems with other versions of similar distributions.

In both cases an installation of XUUDB installs both XUUDB Server and XUUDB admin client.

After installing the server you will have to configure it. This is described in the section Section 3.

2.1 Installation from Core Server Bundle

Download the core server bundle from the UNICORE project website at https://sourceforge.net/projects/unicore/files/Servers/Core

2.2 Installation from RPM or DEB packages

An up-to-date list of the available repositories is given on the following page https://sourceforge.net/p/unicore/wiki/Linux_Repositories/

The preferred way is to use Yum or APT to install (and subsequently update) XUUDB.

After the repository is configured, the following command installs XUUDB:

```
$> yum install unicore-xuudb
or in case of Debian systems
```

\$> apt-get install unicore-xuudb

3 The XUUDB server

3.1 Security

Usually, client-authenticated SSL is used to protect the XUUDB. For this you will need certificates for the XUUDB server and all Grid components that want to talk to the XUUDB. In general the UNICORE servers (like UNICORE/X) and the XUUDB-admin client need to connect to the XUUDB-server. To make SSL connections possible, you have to put the following certificates as trusted certs into the XUUDB's server truststore:

- CA certificate(s) of the UNICORE/X server(s) that query the XUUDB
- CA certificate(s) of the XUUDB-admin user certificate(s)

and XUUDB's CA certificate in the truststores of its clients.

XUUDB server may be run using a plain HTTP port. Then there is no access control at all, so this mode is useful only in environments where XUUDB port is fully protected otherwise against unauthorised access.

3.2 Administrative access

The XUUDB provides two kinds of web service interfaces, one for querying the XUUDB (i.e. mapping UNICORE users to local UNIX users), and a second one for administration of the XUUDB (i.e. adding and editing entries). All access to the XUUDB (including the administration utility!) is through these web services. To prevent arbitrary users from modifying the XUUDB, the administrative interface has to be protected.

To protect the administrative interface, an ACL file is used, which is a plain text file containing the distinguished names of the administrators. At least, it has to contain the DN of the certificate used by the administration utility.

As the static XUUDB data is rather sensitive (at least if privacy of the users is a concern) and dynamic mappings often require some local modifications (e.g. assigning an account from a pool) it is often desirable to protect also the query operations. The XUUDB server offers such an option (see Section 3.3.1).

The ACL file can be changed at runtime to easily add or remove administrators.

To change the location of the ACL file, edit the server configuration and set a configuration parameter (see Section 3.3.1).

The ACL entries are expected in the RFC 2253 format. To get the name of a certificate in the correct format using openssl, you can use the following OpenSSL command:

```
\rightarrow openssl x509 -in demouser.pem -noout -subject -nameopt \leftarrow RFC2253
```

3.3 Configuration

By default, the configuration is defined in the file CONF/xuudb_server.conf. To use a different configuration file, edit the start script, or use --start <config_file> as command line arguments when starting.

The server's configuration file allows for setting the general XUUDB settings, database backend settings, advanced HTTP server settings and finally (for secure HTTPS URLs) the server's truststore and credential. The available properties are described in the following sections.

For production deployments you should review the listen address and setup correctly truststore and credential. Defaults for the embedded database configuration and HTTP server settings are usually fine. In case if you plan to use dynamic mappings, also the dynamic mapping rules need to be provided.

3.3.1 Base server settings

Property name	Type	Default	Description
		value /	
		mandatory	
xuudb.aclFile	filesystem path	-	File with DNs of clients
			authorised to access
			protected XUUDB services.
xuudb.address	string	http://lo	CHIHPStor HIMPBURL
			where the server should
			listen.
xuudb.db.[.*]	string can have	-	Properties with this prefix
	subkeys		are used to configure
			database backend, used by
			XUUDB. See separate
			documentation for details.
xuudb.dynamicAttr	i files yestem pathg	conf/dyna	mFile with iconfiguration.ofml
			the dynamic part of the
			XUUDB.
xuudb.protectAll	[true, false]	false	If true then access to both
			query and modify
			operations are protected by
			ACL. If false then only
			modification operations are
			protected.
xuudb.type	[dn]	dn	DEPRECATED and no
			longer required.

3.3.2 Database settings

The XUUDB can be configured to use different database backends. Currently an embedded H2 database and external MySQL are supported. H2 database (the default) requires no additional configuration actions. In any case XUUDB will automatically create the required database tables.

For MySQL you have to properly set up the server and create a database. After installing and starting the MySQL server login to its using MySQL client as administrator and using a commands similar to the below ones, create a database and assign full access to a xuudb user.

create database xuudb;

```
grant all on xuudb.* to 'xuudbuser'@'127.0.0.1' identified \leftrightarrow by 'pass';
```

Of course you are free to choose different names for the user, password and database. If XU-UDB server is installed on other host then the proper address must be set instead of localhost.

Use the following properties to configure database connection from the XUUDB server. In case of external database pay attention to enter proper values.

Property name	Туре	Default value / mandatory	Description
	Data	ıbase	-
xuudb.db.dialect	[h2, mysql]	h2	Database SQL dialect.
			Must match the selected
			driver, however sometimes
			more then one driver can be
			available for a dialect.
xuudb.db.driver	Class extending	org.h2.Dr	i Database driver class name.
	java.sql.Driver		This property is optional -
			if not set, then a default
			driver for the chosen
			database type is used.
xuudb.db.jdbcUrl	string	jdbc:h2:d	a DatabasedIDB C URL.
xuudb.db.password	string	empty	Database password.
		string	
xuudb.db.username	string	sa	Database username.

3.3.3 Configuring advanced HTTP server settings

UNICORE servers are using an embedded Jetty HTTP server. In most cases the default configuration should be perfectly fine. However, for some sites (e.g. experiencing an extremely high load) HTTP server settings can be fine-tuned with the following parameters.

Property name	Туре	Default value / mandatory	Description
xuudb.httpServer	.Comingallowed	eaders	CORS: comma separated
			list of allowed HTTP
			headers (default: any)
xuudb.httpServer	.Comingallowed	1eCilib∂dBUT,P	OCORSE ICEMENAHSE PAIR atted
			list of allowed HTTP verbs.
xuudb.httpServer	.Comingallowed	rigins	CORS: allowed script
			origins.

Property name	Type	Default	Description
		value /	
would http://www.	Chara folical a Dro	mandatory	COPS: whather proflight
xuudb.httpServer.	Curue, tansernere	THORSE	CORS: whether preflight OPTION requests are
			chained (passed on) to the
			resource or handled via the
			CORS filter.
xuudb.httpServer.	C STRiBg exposedF	e Baodeartsion,	
			list of HTTP headers that
			are allowed to be exposed
		- 1	to the client.
xuudb.httpServer.	d stsuag ledCiphe		Space separated list of SSL
		string	cipher suites to be disabled.
			Names of the ciphers must
			adhere to the standard Java
			cipher names, available
			here:
			http://docs.oracle.com/- javase/8/docs/technotes/-
			guides/security/-
			SunProviders.html#SupportedCipherSuites
xuudb.httpServer.	afterinal fortrails	false	Control whether
Addad.neepberver.	C function	14150	Cross-Origin Resource
			Sharing is enabled. Enable
			to allow e.g. accesing
			REST services from
			client-side JavaScript.
xuudb.httpServer.	e ftakel fallsel s	false	Control whether HTTP
1			strict transport security is
			enabled. It is a good and
			strongly suggested security
			mechanism for all
			production sites. At the
			same time it can not be
			used with self-signed or not
			issued by a generally
			trusted CA server
			certificates, as with HSTS a
			user can't opt in to enter
			such site.
xuudb.httpServer.	f Extreme Earlisse m	false	Use insecure, but fast
			pseudo random generator to
			generate session ids instead
			of secure generator for SSL
			sockets.

Property name	Туре	Default value /	Description
		mandatory	
xuudb.httpServer.	g įtiųe, £ahse ble	false	Controls whether to enable compression of HTTP responses.
xuudb.httpServer.	g intęgeninuabe ipS	i ≽ @0000	Specifies the minimal size of message that should be compressed.
xuudb.httpServer.	h ingegeo aukabem e	c200ns	deprecated
xuudb.httpServer.	linnæges⊅च1ceMa	xI00eTime	deprecated
xuudb.httpServer.			Maximum number of incoming connections to this server. If set to a value larger than 0, incoming connections will be limited to that number. Default is 0 = unlimited.
xuudb.httpServer.	m intdgeli ≥≅ il me	200000	Time (in ms.) before an idle connection will time out. It should be large enough not to expire connections with slow clients, values below 30s are getting quite risky.
xuudb.httpServer.		255	Maximum number of threads to have in the thread pool for processing HTTP connections. Note that this number will be increased with few additional threads to handle connectors.
xuudb.httpServer.		1 Atuthe	Minimum number of threads to have in the thread pool for processing HTTP connections. Note that this number will be increased with few additional threads to handle connectors. Controls whether the SSL socket requires client-side
xuudb.httpServer.	w {truteÇ false r t Aut	htbrue	authentication. Controls whether the SSL socket accepts (but does not require) client-side authentication.

Property name	Type	Default	Description
		value /	
		mandatory	
xuudb.httpServer.	x Mriag eAllowed	http://lo	clard one in that is allowed
			to embed web interface
			inside a (i)frame.
			Meaningful only if the
			xFrameOptions is set to
			allowFrom. The value
			should be in the form:
			http[s]://host[:port]
xuudb.httpServer.	x [deam ,eOptions	deny	Defines whether a
	sameOrigin,		clickjacking prevention
	allowFrom,		should be turned on, by
	allow]		insertionof the
			X-Frame-Options HTTP
			header. The <i>allow</i> value
			disables the feature. See the
			RFC 7034 for details. Note
			that for the <i>allowFrom</i> you
			should define also the
			xFrameAllowed option and
			it is not fully supported by
			all the browsers.

Example

Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

In this example we will turn on compression of all responses bigger then 50kB (assuming that the client supports decompression). Additionally we are limiting the number of concurrent clients that can be served to more or less 50, while keeping 10 threads ready all the time to server new clients quicker.

```
jetty.gzip.enable=true
jetty.gzip.minGzipSize=51200
jetty.maxThreads=50
jetty.minThreads=10
```

3.3.4 Configuring PKI trust settings

Public Key Infrastructure (PKI) trust settings are used to validate certificates. This is performed, in the first place when a connection with a remote peer is initiated over the network, using the SSL (or TLS) protocol. Additionally certificate validation can happen in few other situations, e.g. when checking digital signatures of various sensitive pieces of data.

Certificates validation is primarily configured using a set of initially trusted certificates of so called Certificate Authorities (CAs). Those trusted certificates are also known as *trust anchors* and their collection is called a *trust store*.

Except of *trust anchors* validation mechanism can use additional input for checking if a certificate being checked was not revoked and if its subject is in a permitted namespace.

UNICORE allows for different types of trust stores. All of them are configured using a set of properties.

- *Keystore trust store* the only format supported in older UNICORE versions. Trusted certificates are stored in a single binary file in JKS or PKCS12 format. The file can be only manipulated using a special tool like JDK *keytool* or openssl (in case of PKCS12 format). This format is great if trust store should be in a single file or when compatibility with other Java solutions or older UNICORE releases is desired.
- *OpenSSL trust store* allows to use a directory with CA certificates stored in PEM format, under precisely defined names: the CA certificates, CRLs, signing policy files and namespaces files are named <hash>.0, <hash>.r0, <hash>.signing_policy and <hash>.namespaces. Hash is the old hash of the trusted CA certificate subject name (in Openssl version > 1.0.0 use -suject_hash_old switch to generate it). If multiple certificates have the same hash then the default zero number must be increased. This format is the same as used by other then UNICORE popular middlewares as Globus and gLite. It is suggested when a common trust store with such middlewares is needed.
- *Directory trust store* the most flexible and convenient option, suggested for all remaining cases. It allows to use a list of wildcard expressions, concrete paths of files or even URLs to remote files as a set of trusted CAs and in the same way for the CRLs. With this trust store administrator can simply configure all files (or all with a specified extension) in a directory to be used as a trusted certificates.

In all cases trust stores can be (and by default are) configured to be automatically refreshed.

Property name	Туре	Default value / mandatory	Description
xuudb.truststore.	a [AbloDW;xy DENY]	ALLOW	Controls whether proxy certificates are supported.
xuudb.truststore.	t [kæystore, openssl, directory]	mandatory to be set	The truststore type.

Property name	Туре	Default	Description
		value /	•
		mandatory	
xuudb.truststore.	u indegee ii umber va	1600	How often the truststore
			should be reloaded, in
			seconds. Set to negative
			value to disable refreshing
			at runtime. (runtime
			updateable)
		ype settings	
xuudb.truststore.	dinteget ourybern	le lc 5ionTime	OConnection timeout for
			fetching the remote CA
	1611 .		certificates in seconds.
xuudb.truststore.	d in hesystem poiths k	CachePath	Directory where CA
			certificates should be
			cached, after downloading
			them from a remote source. Can be left undefined if no
			disk cache should be used.
			Note that directory should
			be secured, i.e. normal
			users should not be allowed
			to write to it.
xuudb.truststore.	d iPEM t DER Inco		For directory truststore
		3	controls whether
			certificates are encoded in
			PEM or DER. Note that the
			PEM file can contain
			arbitrary number of
			concatenated,
			PEM-encoded certificates.
xuudb.truststore.		t-ions.*	List of CA certificates
	properties with		locations. Can contain
	a common		URLs, local files and
	prefix		wildcard expressions.
			(runtime updateable)
	Keystore ty		The second second
xuudb.truststore.	k stying oreForma	t-	The keystore type (jks,
			pkcs12) in case of truststore
		1	of keystore type.
xuudb.truststore.	к shynag orePassw	ro-rd	The password of the
	lating D		keystore type truststore.
xuudb.truststore.	к shynag orePath	-	The keystore path in case of
	On an act to	na sattimas	truststore of keystore type.
	Openssi ty	pe settings	

Property name	Туре	Default	Description
		value /	
		mandatory	
xuudb.truststo	ce.o ftene ș falst ∳wSto	r £ absenat	In case of openssl
			truststore, specifies whether
			the trust store is in openssl
			1.0.0+ format (true) or
			older openssl 0.x format
			(false)
xuudb.trustston	re.ofGhOBUSsEbbG	RHDRWIA DPMA	LALCASE of openssl
	EU-		truststore, controls which
	GRIDPMA_GLO	BUS.	(and in which order)
	GLOBUS,	,	namespace checking rules
	EUGRIDPMA,		should be applied. The
		SIDPMA REO	U RHQ UIRE settings will
	EU-	CIDI WII I_KEQ	cause that all configured
		DIIC DEOIIIE	Enamespace definitions files
		_ ~	
	GLOBUS_REQU	JIKE,	must be present for each
	EU-		trusted CA certificate
	GRIDPMA_REQ	UIRE,	(otherwise checking will
	EU-		fail). The AND settings will
	GRIDPMA_ANI	_GLOBUS,	cause to check both existing
	EU-		namespace files. Otherwise
		_GLOBUS_R	EQNETIRE, found is checked
	IGNORE]		(in the order defined by the
			property).
xuudb.truststo	ce.ofikensysstelm path	/etc/grid	-Dinectorytty/becused foircate
			opeenssl truststore.
	Revocation	on settings	
xuudb.truststo	ce . cintegen nemberor	T15meout	Connection timeout for
			fetching the remote CRLs
			in seconds (not used for
			Openssl truststores).
xuudb.truststoi	ce.cfileByisterni pathe	ath	Directory where CRLs
	J 1		should be cached, after
			downloading them from
			remote source. Can be left
			undefined if no disk cache
			should be used. Note that
			directory should be
			•
			secured, i.e. normal users
			should not be allowed to
			write to it. Not used for
			Openssl truststores.

Property name	Туре	Default value / mandatory	Description
xuudb.truststore		*-	List of CRLs locations. Can
	properties with		contain URLs, local files
	a common		and wildcard expressions.
	prefix		Not used for Openssl
			truststores. (runtime
			updateable)
xuudb.truststore		IF_VALID	General CRL handling
	IF_VALID,		mode. The IF_VALID
	IGNORE]		setting turns on CRL
			checking only in case the
			CRL is present.
xuudb.truststore	e.cintegedatumberte	r&@0	How often CRLs should be
			updated, in seconds. Set to
			negative value to disable
			refreshing at runtime.
			(runtime updateable)
xuudb.truststore	e.omsegea obneberl	3600	For how long the OCSP
			responses should be locally
			cached in seconds (this is a
			maximum value, responses
			won't be cached after
	C1 - 1 - 1 - 11		expiration)
xuudb.truststore	e. o to kepsysteenk op atch he	-	If this property is defined
			then OCSP responses will
			be cached on disk in the
11	1' af 3.5	1	defined folder.
xuudb.truststore		onders. <nu< td=""><td>MOptional list of local OCSP</td></nu<>	MOptional list of local OCSP
	properties with		responders
	a common		
	prefix	TD 3573 TT 3	Canonal OCCD also also a
xuudb.truststore			BGeneral OCSP ckecking
	IF_AVAILABLE		mode. REQUIRE should
	IGNORE]		not be used unless it is
			guaranteed that for all
			certificates an OCSP
db +a+a+	interité munh :	10000	responder is defined. Timeout for OCSP
xuudb.truststore	e.ousegermemoder	10000	1
	[CDLACCDA	-000D 0D1	connections in miliseconds.
xuudb.truststore	OCSP CRL	leurusp_CRL	Controls overal revocation
	OCSP_CKL]		sources order

Property name	Type	Default	Description
		value /	
		mandatory	
xuudb.truststore.	r (truce; fatlsie) nUse	Affallse	Controls whether all
			defined revocation sources
			should be always checked,
			even if the first one already
			confirmed that a checked
			certificate is not revoked.

Examples

Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Directory trust store, with a minimal set of options:

```
truststore.type=directory
truststore.directoryLocations.1=/trust/dir/*.pem
truststore.crlLocations=/trust/dir/*.crl
```

Directory trust store, with a complete set of options:

```
truststore.type=directory
truststore.allowProxy=DENY
truststore.updateInterval=1234
truststore.directoryLocations.1=/trust/dir/*.pem
truststore.directoryLocations.2=http://caserver/ca.pem
truststore.directoryEncoding=PEM
truststore.directoryConnectionTimeout=100
truststore.directoryDiskCachePath=/tmp
truststore.crlLocations.1=/trust/dir/*.crl
truststore.crlLocations.2=http://caserver/crl.pem
truststore.crlUpdateInterval=400
truststore.crlMode=REQUIRE
truststore.crlConnectionTimeout=200
truststore.crlDiskCachePath=/tmp
```

Openssl trust store:

```
truststore.type=openssl
truststore.opensslPath=/truststores/openssl
truststore.opensslNsMode=EUGRIDPMA_GLOBUS_REQUIRE
```

```
truststore.allowProxy=ALLOW
truststore.updateInterval=1234
truststore.crlMode=IF_VALID
```

Java keystore used as a trust store:

```
truststore.type=keystore
truststore.keystorePath=src/test/resources/certs/truststore. 
    jks
truststore.keystoreFormat=JKS
truststore.keystorePassword=xxxxxx
```

3.3.5 Configuring the credential

UNICORE uses private key and a corresponding certificate (called together as a *credential*) to identify users and servers. Credentials might be provided in several formats:

- Credential can be obtained from a *keystore file*, encoded in JKS or PKCS12 format.
- Credential can be loaded as a pair of PEM files (one with private key and another with certificate),
- or from a pair of DER files,
- or even from a single file, with PEM-encoded certificates and private key (in any order).

The following table list all parameters which allows for configuring the credential. Note that nearly all options are optional. If not defined, the format is tried to be guessed. However some credential formats require additional settings. For instance if using *der* format the *keyPath* is mandatory as you need two DER files: one with certificate and one with the key (and the latter can not be guessed).

Property name	Type	Default	Description
		value /	
		mandatory	
xuudb.credential.	patesystem path	mandatory	Credential location. In case
		to be set	of jks, pkcs12 and pem store
			it is the only location
			required. In case when
			credential is provided in
			two files, it is the certificate
			file path.

Property name	Туре	Default	Description
		value / mandatory	
xuudb.credential.	f (jks), aptkes 12, der, pem]	-	Format of the credential. It is guessed when not given. Note that <i>pem</i> might be either a PEM keystore with certificates and keys (in PEM format) or a pair of PEM files (one with
xuudb.credential.	p atsing ord	-	certificate and second with private key). Password required to load
xuudb.credential.	k stying th	-	the credential. Location of the private key if stored separately from the main credential (applicable for <i>pem</i> and <i>der</i>
xuudb.credential.	k stying ssword	-	types only), Private key password, which might be needed only for <i>jks</i> or <i>pkcs12</i> , if key is encrypted with different password then the main credential password.
xuudb.credential.	k stying ias	-	Keystore alias of the key entry to be used. Can be ignored if the keystore contains only one key entry. Only applicable for <i>jks</i> and <i>pkcs12</i> .

Examples

Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Credential as a pair of DER files:

```
credential.format=der
credential.password=the\!njs
credential.path=/etc/credentials/cert-1.der
```

```
credential.keyPath=/etc/credentials/pk-1.der
```

Credential as a JKS file (credential type can be autodetected in almost every case):

```
credential.path=/etc/credentials/server1.jks
credential.password=xxxxxx
```

3.4 Dynamic mappings configuration

Dynamic mappings are configured with a set of rules. When designing rules it is good to remember that all users, which will be evaluated, were already successfully authorized.

Each rule has a condition which selects users and a list of mappings which should be applied for the selected users. Example conditions (in English):

- all members of a /vo.wonderworld.gov
- all (authorized) users
- all users having extra attribute *matlabAllowed* with any value AND being member of a subgroup of /vo.wonderworld.gov/dynamic/

Example mappings (in English):

- add user a supplementary group matlab
- · assign uid from a pool of existing uids
- assign a fixed gid grid
- invoke an external program and use its standard output as users gid

Precisely speaking, a mapping must have defined:

- what attribute it maps: *uid*, (primary)*gid* or *supplementaryGids*,
- using what method: fixed, pool or script

Additionally one can define an optional parameter stating if the mapping should overwrite an attribute value which was previously set (either by an earlier rule or assigned using a different attribute source).

As it was mentioned there are three kinds of mappings. Let's shortly introduce them one by one.

3.4.1 Fixed mappings

Fixed mappings are the most basic option. The mapping is formed by a simple assignment of a fixed value. It can be used to:

- assign a common (shared!) uid to selected users (rarely used)
- assign a fixed gid to selected users (very useful to assign a gid to all Grid users, or all members of a VO)
- assign some supplementary gids to selected users (useful to provide additional local permissions to users having a special role/attributes/etc.).

The example in the pool mappings section contains also a fixed mapping.

3.4.2 Script mappings

Script mappings are the "Do It Yourself" mechanism. You can provide a command line which will be parsed and invoked. The application must return (on its standard output) a string with a mapping result (depending on what is mapped - gid, uid or a space separated list of supplementary gids). Of course the script can be informed who is actually being mapped, by using parameters enclosed in \${}. The list of available parameters is given below.

- userDN user's DN
- issuerDN user's certificate issuer's DN
- role user's role
- vo user's selected VO
- extraAttributes map with extra attributes, names are the keys
- xlogin user's uid (if already established)
- gid user's gid (if already established)
- supplementaryGids user's supplementary gids (if already established)
- xloginSet whether uid was set
- gidSet whether gid was set
- dryRun whether the current invocation is only a simulation, and shouldn't affect any persisted system settings.

The example below contains also a script mapping.

3.4.3 Pool mappings

Finally the *pool mappings* are both flexible and relatively easy to use --- it is the most advanced mapping type. Using the pool mapping you have to prepare a set of reserved identifiers (uids or gids depending on what is mapped). The related system accounts can be precreated or can be created on-demand. The pool mapping is configured with an additional, very important parameter: pool key. Pool key is a name of one of the user's attributes: *userDN*, *issuerDN* (DN of CA which issued user's certificate), *role*, *vo* or any other generic user's attribute.

To explain how the pool works let's assume that key is set to *userDN*. Then the pool will map a user as follows: first it is checked if there is an existing mapping bound to the user's DN. If it is found then it is simply returned. If not (the user is trying to use the site for the first time) a new identifier is selected from the pool, and stored under the key being the user's DN. Then the new identifier is returned.

Therefore all users having the same value of the pool key will get the same mapping and vice versa. If DN is the key then all users will have a distinct mapping (useful for uids or for gids, if every user should get a unique one). If for instance a VO is the key then all VO members will have the same mapping (useful for gid, or for uid if all VO members should have the same user account).

The following example should help to understand those concepts and is also providing a basic syntax reference:

```
<?xml version="1.0" encoding="UTF-8"?>
<dynamicAttributes xmlns="http://unicore.eu/xuudb/ ←</pre>
   dynamicAttributesRules"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <rules>
    <!-- all members of the vo /vo.wonderworld.gov should have a
       common uid 'shared_user'-->
    <rule>
      <condition>vo.matches("/vo.wonderworld.gov/.*")</condition>
      <mapping type="fixed" maps="uid">shared_user</mapping>
    </rule>
    <!-- all users with a role 'admin' should get a primary gid \leftrightarrow
       from the 'admins-pool' pool.
    For pools the 'maps' parameter is optional - it is better to \,\,\,\,\,\,\,\,
       specify it in the pool definition,
    below. -->
    <rule>
      <condition>role="admin"</condition>
      <mapping type="pool">admins-pool</mapping>
    </rule>
    <!-- all users from the /biology VO get an uid from the pool \,\leftrightarrow
        and a fixed primary gid 'biol' -->
    <rule>
```

```
<condition>vo.matches("/biology/.*")</condition>
      <mapping type="pool">biology-uids-pool</mapping>
      <mapping type="fixed" maps="gid">biol</mapping>
    </rule>
    <!-- complicated condition: all users who have a generic \ensuremath{\hookleftarrow}
        attribute 'matlabAllowed' set AND the value
        of this attribute is 'true' get a supplementary group ' \leftarrow
            matlab' -->
    <rule>
      <condition>attributes["matlabAllowed"] != null and attributes \leftarrow
          ["matlabAllowed"].contains("true")</condition>
      <mapping type="fixed" maps="supplementaryGids">matlab</ \leftarrow
          mapping>
    </rule>
    <!-- all (authorized) users, who do not have an uid set ( \hookleftarrow
        overwriteExisting=false)
        should have an uid assigned by a script /usr/local/bin/ \leftarrow
            create-mapping.pl. The script will be called
        with two arguments: user's DN and VO.
    <rule>
      <condition>true</condition>
      <mapping type="script" maps="uid" overwriteExisting="false">/ ←
          usr/local/bin/create-mapping.pl "${userDN}" "${vo}" </ \hookleftarrow
          mapping>
    </rule>
  </rules>
  <!-- Here come pools -->
  <pools>
    <!-- pool 'admins-pool' maps gids. The list of gids provides \,\leftarrow\,
        groups which were
    pre-created in the system. The gids will be stored per-user dn, \hookleftarrow
        so every admin will get another group.
    Finally the list of gids uses special expressions where number \ \leftarrow
       ranges are provided.
    <pool id="admins-pool" type="gid" key="dn" precreated="true">
      <id>admin_grp[1-100]</id>
      <id>admin_grp[200-1000]</id>
    </pool>
    <!-- This pool identifiers are loaded from an external file -->
    <pool id="biology-uids-pool" type="uid" key="dn" precreated=" ←
      <file>src/test/resources/externalUidsPool</file>
    </pool>
  </pools>
</dynamicAttributes>
```

Usage of pools brings several issues regarding old mappings removal and notifications about pools getting empty. In the first case it suggested not to remove the users for the time a VO or Grid is supported: it is a simplest approach, and nowadays operating systems can support thousands of uids without any problem (Linux can have 32bit uid numbers).

In case a site wants to recycle mappings, XUUDB offers the following mechanism:

- Inactive mappings can be automatically (after a configurable time threshold) or manually (using the admin client) *frozen*. An identifier belonging to a frozen mapping is still assumed to be occupied, but the mapped user won't have it assigned (in the unprobable case that she returns to the site). Freezing is introduced to give a time for tidying up local resources assigned to the identifier. Such cleaning must be done manually and should include removal of all owned files and killing any processes. Of course this depends whether the identifier was a gid or uid. Also please note that in case of clusters, all nodes should be cleaned up.
- After the clean up is done, the frozen mapping can be removed, again manually using the admin client or automatically, after staying in the frozen state for a specified amount of time. Note that it is impossible to remove an alive mapping.

If administrator is able to provide scripts which performs cleanup, then it is possible to invoke them upon pool mapping freezing and automate the whole process. In a similar way other handlers may be configured and XUUDB will invoke them to notify about mappings removal, assignment of a new mapping (useful when accounts are not pre-created but should be created on demand) and also when a pool is getting empty.

The following example shows all the possible handlers and lists arguments which are passed to them. As it can be seen all pool options including handlers, can be configured globally or per-pool.

```
<?xml version="1.0" encoding="UTF-8"?>
<dynamicAttributes xmlns="http://unicore.eu/xuudb/ ←</pre>
   dynamicAttributesRules"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!-- how often (in s) pools should be checked for old or inactive \hookleftarrow
      mappings -->
  <poolMonitoringDelay>300</poolMonitoringDelay>
  <defaultConfiguration>
        <!-- in seconds: automatic freezeing (time measured from \ensuremath{\leftarrow}
            last mapping use)... -->
        <automaticFreezeAfter>3600000</automaticFreezeAfter>
        <!-- ... and final removal (time measurd from mapping
            freeze) -->
        <automaticDeleteAfter>36000</automaticDeleteAfter>
        <!-- when less then this free mappings are left generate a
            warning -->
        <emptyWarningAbsolute>20</emptyWarningAbsolute>
        <!-- when less then this percent of free mappings is left \,\,\hookleftarrow
            generate a warning -->
        <emptyWarningPercent>5</emptyWarningPercent>
```

```
<!-- timeout for running ALL external programms -->
        <handlerInvocationTimeLimit>10000</ ←
                  handlerInvocationTimeLimit>
        <!-- Various handlers. Arguments are pool.getId(), pool. \leftarrow
                  getType().toString(),
                                                                                                    bean.getEntry(), oldSec+"" \leftarrow
        <!-- Handler invoked before freezing an account.
Arguments: <poolId> <poolType> <identifier> < ←
          inactiveForInSeconds>
If handler returns a non-zero exit status then the freezing is \hookleftarrow
             skipped
(unless invoked by admin-client).
        \mbox{\countResources} \leftarrow \mbox{\countResourc
                   .sh</handlerAboutToFreeze>
        <!-- Handler invoked before deleting a frozen identifier.
                      Arguments: <poolId> <poolType> <identifier> < \leftarrow
                                 frozenForInSeconds>
                      If handler returns a non-zero exit status then the \ \leftarrow
                                deletion is skipped
                       (unless invoked by admin-client).
        {\bf <}handlerAboutToDelete>/opt/handlers/notifyAccountRecycled. \leftarrow
                  sh</handlerAboutToDelete>
        <!-- Handler invoked when an identified from the uids pool \,\leftarrow
                  is going to be used for the first time
         (or for the first time after deleting it), if the pool is \leftrightarrow
                  set as not pre-created.
                               Arguments: <poolId> <uid> <key>
        <handlerCreateSystemUid>/opt/handlers/adduser.sh</ \leftarrow
                  handlerCreateSystemUid>
        <!-- Handler invoked when an identified from the gids pool \,\,\,\,\,\,\,\,\,\,
                  is going to be used for the first time
         (or for the first time after deleting it), if the pool is \,\,\,\,\,\,\,\,
                  set as not pre-created.
                               Arguments: <poolId> <gid> <key>
        <handlerCreateSystemGid>/opt/handlers/addgroup.sh
                  handlerCreateSystemGid>
        <!-- Handler invoked when a pool warning threshold is \ \leftarrow
                  exceeded.
```

```
Arguments: <poolId> <poolType> <remainingFreeIds>
        <handlerPoolGettingEmpty>/opt/handlers/notifyNearlyEmpty.sh \leftarrow
            </handlerPoolGettingEmpty>
        <!-- Handler invoked when a pool gets empty.
             Arguments: <poolId> <poolType>
        <handlerPoolEmpty>/opt/handlers/notifyEmpty.sh</ \leftarrow
           handlerPoolEmpty>
  </defaultConfiguration>
        <!-- some rules ..... -->
  </rules>
  <pools>
        <!-- Pool can overwrite any of the global configuration \,\leftarrow\,
           options -->
    <pool id="admins-pool" type="gid" key="dn" precreated="true">
      <configuration>
         <!-- disable automatic freezing for this pool -->
                 <automaticFreezeAfter>-1</automaticFreezeAfter>
      </configuration>
      <id>admin_grp[1-100]</id>
      <id>admin_grp[200-1000]</id>
    </pool>
  </pools>
</dynamicAttributes>
```

3.5 Starting the XUUDB server

Start the server with

BIN/start.sh

In case if XUUDB was installed with binary package use:

/etc/init.d/unicore-xuudb start

3.6 Stopping the server

Stop the server with

BIN/stop.sh

This sends a TERM signal to the XUUDB process. Please do not use kill -9 to stop XU-UDB, to avoid corrupting the database.

In case if XUUDB was installed with binary package use:

```
/etc/init.d/unicore-xuudb stop
```

3.7 Logging

UNICORE uses the Log4j logging framework. It is configured using a config file. By default, this file is found in components configuration directory and is named logging.properties. The config file is specified with a Java property log4j.configuration (which is set in startup script).

Several libraries used by UNICORE also use the Java utils logging facility (the output is two-lines per log entry). For convenience its configuration is also controlled in the same logging.properties file and is directed to the same destination as the main Log4j output.

Note

You can change the logging configuration at runtime by editing the logging properties file. The new configuration will take effect a few seconds after the file has been modified.

By default, log files are written to the the LOGS directory.

The following example config file configures logging so that log files are rotated daily.

```
# Set root logger level to INFO and its only appender to A1.
log4j.rootLogger=INFO, A1

# A1 is set to be a rolling file appender with default params
log4j.appender.A1=org.apache.log4j.DailyRollingFileAppender
log4j.appender.A1.File=logs/uas.log

#configure daily rollover: once per day the uas.log will be copied
#to a file named e.g. uas.log.2008-12-24
log4j.appender.A1.DatePattern='.'yyyy-MM-dd

# A1 uses the PatternLayout
log4j.appender.A1.layout=org.apache.log4j.PatternLayout
log4j.appender.A1.layout.ConversionPattern=%d [%t] %-5p %c{1} %x - 
%m%n
```

Note

In Log4j, the log rotation frequency is controlled by the DatePattern. Check http://logging.apache.org/log4j/1.2/apidocs/org/apache/log4j/DailyRollingFileAppender.html for the details.

For more info on controlling the logging we refer to the log4j documentation:

- PatternLayout
- RollingFileAppender
- DailyRollingFileAppender

Log4j supports a very wide range of logging options, such as date based or size based file rollover, logging different things to different files and much more. For full information on Log4j we refer to the publicly available documentation, for example the Log4j manual.

3.7.1 Logger categories, names and levels

Logger names are hierarchical. In UNICORE, prefixes are used (e.g. "unicore.security") to which the Java class name is appended. For example, the XUUDB connector in UNICORE/X logs to the "unicore.security.XUUDBAuthoriser" logger.

Therefore the logging output produced can be controlled in a fine-grained manner. Log levels in Log4j are (in increasing level of severity):

TRACE on this level *huge* pieces of unprocessed information are dumped, # DEBUG on this level UNICORE logs (hopefully) admin-friendly, verbose information, useful for hunting problems, # INFO standard information, not much output, # WARN warnings are logged when something went wrong (so it should be investigated), but recovery was possible, # ERROR something went wrong and operation probably failed, # FATAL something went really wrong - this is used very rarely for critical situations like server failure.

For example, to debug a security problem in the UNICORE security layer, you can set:

```
log4j.logger.unicore.security=DEBUG
```

If you are just interested in details of credentials handling, but not everything related to security you can use the following:

```
log4j.logger.unicore.security=INFO
log4j.logger.unicore.security.CredentialProperties=DEBUG
```

so the XUUDBAuthoriser will log on DEBUG level, while the other security components log on INFO level.

Note

(so the full category is printed) and turn on the general DEBUG logging for a while (on unicore). Then interesting events can be seen and subsequently the logging configuration can be fine tuned to only show them.

Several logging categories common in XUUDB:

Log category	Description
unicore	All of UNICORE
unicore.security	Security layer
unicore.client	Client calls (to other servers)
unicore.xuudb	XUUDB related
unicore.xuudb.server	XUUDB server
unicore.xuudb.server.db	XUUDB server database layer
unicore.xuudb.client	XUUDB admin client

4 The admin client

The admin client is used to edit the XUUDB, using a web service interface. It is configured in the file CONF/xuudb_client.conf. Client is invoked using the following pattern:

ADMIN <command> <options>

You can get detailed usage info by calling the admin script without any options. As it was noted above the actual utility path is dependent on how XUUDB was installed: it is either /usr/sbin/unicore-xuudb-admin or INST/bin/admin.sh.

Note

to switch on the confirmation message asked by the add command, edit the admin.sh script, so that the xuudb.batch property is set to false.

The client configuration requires the URL of the XUUDB server in the property xuudb.address and in case of secure HTTPS connections also a configuration truststore and credential. The settings are exactly the same as in case of the XUUDB server, so refer to its documentation: Section 3.3.4.

4.1 Configuring advanced HTTP client settings

UNICORE client stack can be configured with several advanced options. In most cases you can skip this section as defaults are fine.

The following table lists all available options. A special note for the *http*.* properties: those are passed to the Apache Commons HTTP Client library. Therefore it is possible to configure all relevant options of the client. The options are listed under this address: http://hc.apache.org/httpclient-3.x/preference-api.html Also see the example below.

Property name	Туре	Default value / mandatory	Description
xuudb.client.digi			Controls whether signing of key web service requests should be performed.
xuudb.client.http		false	Whether HTTP basic authentication should be used.
xuudb.client.http	P atsing ord	empty string	Password for use with HTTP basic authentication (if enabled).
xuudb.client.http	Usteing	empty string	Username for use with HTTP basic authentication (if enabled).
xuudb.client.inHa	n string s	empty string	Space separated list of additional handler class names for handling incoming WS messages
xuudb.client.maxW		3	Controls how many times the client should try to call a failing web service. Note that only the transient failure reasons cause the retry. Note that value of 0 enables unlimited number of retries, while value of 1 means that only one call is tried.
xuudb.client.mess		false	Controls whether messages should be logged (at INFO level).
xuudb.client.outH		empty string	Space separated list of additional handler class names for handling outgoing WS messages
xuudb.client.secu	r[ttue\$fasse]ons	true	Controls whether security sessions should be enabled.

Property name	Туре	Default	Description
		value /	
		mandatory	
xuudb.client.se	rve [MOME ņameChe	cwairing	Controls whether server's
	WARN, FAIL]		hostname should be
			checked for matching its
			certificate subject. This
			verification prevents
			man-in-the-middle attacks.
			If enabled WARN will only
			print warning in log, FAIL
			will close the connection.
xuudb.client.ss	lAu fthreEfalsel ed	true	Controls whether SSL
			authentication of the client
			should be performed.
xuudb.client.ss	l En Etitulee Calse l	true	Controls whether the
	[,]		SSL/TLS connection mode
			is enabled.
xuudb.client.ws	Calinkeeter underberv	10000	Amount of milliseconds to
			wait before retry of a failed
			web service call.
	HTTP clie	nt settings	1
xuudb.client.ht	tp. [tituleo false h] unki	ntgrue	If set to false, then the
			client will not use HTTP
			1.1 data chunking.
xuudb.client.ht	tp.[truenfadste]on-c	lbasese	If set to true then the client
			will send connection close
			header, so the server will
			close the socket.
xuudb.client.ht	tp .integee number. t	in@out	Timeout for the connection
			establishing (ms)
xuudb.client.ht	tp.imategeenRnobere	6	How many connections per
			host can be made. Note:
			this is a limit for a single
			client object instance.
xuudb.client.ht	tp .imategeedumber ts	3	Maximum number of
			allowed HTTP redirects.
xuudb.client.ht	tp.imategeonumber	20	How many connections in
			total can be made. Note:
			this is a limit for a single
			client object instance.
xuudb.client.ht	tp .integeenumber ed	u@	Socket timeout (ms)
HTTP proxy settings			

Property name	Туре	Default value /	Description
xuudb.client.http	.stoingroxyHost	mandatory S-	Space (single) separated list of hosts, for which the HTTP proxy should not be used.
xuudb.client.http	. stringy . passwo	rd	Relevant only when using HTTP proxy: defines password for authentication to the proxy.
xuudb.client.http	.ptringy.user	-	Relevant only when using HTTP proxy: defines username for authentication to the proxy.
xuudb.client.http	.stringyHost	-	If set then the HTTP proxy will be used, with this hostname.
xuudb.client.http	. įntegey Romber	-	HTTP proxy port. If not defined then system property is consulted, and as a final fallback 80 is used.
xuudb.client.http	. string yType	HTTP	HTTP proxy type: HTTP or SOCKS.

Example

Note

Various UNICORE modules use different property prefixes. Here we don't put any, but in practice you have to use the prefix (see the reference table above for the actual prefix). Also properties might need to be provided using different syntax, as XML.

Here we are setting an extremely short connection and socket timeouts for the clients calls, using the Apache HTTP client parameters. Additionally server hostname to certificate subject name checking is set to cause connections failures, preventing man in the middle attacks.

```
client.http.connection.timeout=2000
client.http.socket.timeout=2000
client.serverHostnameChecking=FAIL
```

4.2 Commands

The help with examples is provided for each command. You can use helpAll to print a reference documentation for all commands. Selected commands are also described below.

```
[classic]
  add
  adddn
  check-cert (chc)
 check-dn (chdn)
  export
 import
 list
  remove
 update
[dynamic]
 findMapping (fm)
 findReverseMapping (fr)
 freezeMappings
 getDynamicAttributes (getDyn)
 listMappings (lm)
 listPools (lp)
 removeMappings
 removePool (rmp)
 simulate (sim)
[other]
 help
 helpAll
```

Common options:

gcID

The so-called "grid component ID" is used to group entries, and must match the setting in the UNICORE/X configuration file uas.config. For example if you have two systems with different user name mappings, you can handle both with a single XUUDB, since you can store two user name mappings for each certificate, by choosing a different gcID for both systems. When updating xuudb entries, the special gcid * can be used as wildcard for updating user entries on all systems.

pemfile

A file containing a public key in PEM format

DN

The distinguished name of a user

xlogin

xlogins (from UNIX login) are used for incarnation. Grid user's request which results in

invocation of operations on a target system (usually through BSS) must be mapped to a local UNIX user. This attribute specifies the XLogins which are valid for the user. The first one is also used as a default one, if user does not request a particular one. Multiple logins can be specified using a:

project

Defines a primary group UNIX group for a user. If it is undefined then a default group for the XLogin is used.

role

The usual roles in UNICORE are user for a normal user, and admin for an administrator. Custom roles can be added, and can be assigned permissions in the UNICORE/X security policy file.

4.3 Adding entries using add or adddn

Example using the DN:

```
\ ADMIN adddn DEMO-SITE "CN=John Doe, O=Test Inc" userlogin \ \hookleftarrow user
```

Example using a pem file:

```
$> ADMIN add DEMO-SITE /path/to/usercert.pem userlogin user
```

Note

When extracting the DN from a certificate file using OpenSSL, make sure to use the RFC2253 option, for example:

```
openssl x509 -in demouser.pem -noout -subject -nameopt \leftarrow RFC2253
```

4.4 Checking the content

Apart from list, you can use the check-cert and check-dn commands to see what the XUUDB contains for a certain certificate or DN.

4.5 Removing entries

HINT: before removing you can check with the list command which takes the same parameters, that your are removing the correct entries.

To remove all entries from xuudb (you will have to confirm this)

```
$> ADMIN remove ALL
```

To remove some entries, you have to specify attributes.

To remove a user with cert cert.pem at gcid MYSITE:

```
$> ADMIN remove gcid=id001 pemfile=/path/cert.pem
```

To remove all users from gcid OLDMACHINE:

```
$> ADMIN remove gcid=OLDMACHINE
```

To remove a user with xlogin jdoe from all gcids:

```
$> ADMIN remove xlogin=jdoe
```

etc...

4.6 Exporting/importing

The export command creates a csv file, which will contain the complete XUUDB database:

```
$> ADMIN export uudb.csv
```

If the file already exists, the export tool will complain. To override this, please specify the overwrite option, e.g.

```
$> ADMIN export uudb.csv overwrite
```

The import command takes the a csv file (as generated by export) and imports all entries. Already existing entries will not be changed. To do updates, execute admin.sh remove ALL before, or specify clearDB as a second argument

```
$> ADMIN import uudb.csv
```

4.7 Updating entries

The update command can be used to modify existing entries, for example to replace the certificate or the login. For example,

```
$> ADMIN update DEMO-SITE certs/demouser.pem xlogin=jb007
```

would update the entry identified by the gcID *DEMO-SITE* and the given pem file, and assign a new xlogin. If you want to update a user's entry on all the sites, you would use

```
$> ADMIN update \* certs/demouser.pem xlogin=jb007
```

Note that the wildcard * is a special character for the shell and needs to be escaped with a backslash.